

# eas<sup>y</sup>ret<sup>®</sup>

**577 nm FIBER  
TECHNOLOGY LASER**



**Peripheral and  
Macular Photocoagulation**



**EasYret®** is a fully integrated **577 nm yellow photocoagulator** based on a **technological breakthrough: fiber laser technology**. Available with Haag Streit or Zeiss type slit lamps, it offers a large choice of treatment settings well adapted to the treatment of macular and peripheral retinal pathologies.

## **EASYRET®: YELLOW FIBER LASER, FEATURING MULTISPOT AND SUBLIMINAL® TECHNOLOGIES**


### **Fiber Laser Technology:**

Stemming from the ELBA™ technology, developed and successfully marketed by Quantel Laser for various applications, this new generation of laser cavity provides unique advantages:

- An excellent beam quality ensuring a homogeneous laser spot profile (top hat)
- The emission of pure 577 nm yellow wavelength
- An extended lifetime thanks to a simple, compact and reliable technology.

The fiber laser technology is a variation of the standard solid-state laser technology.

In fiber lasers, the lasing medium is composed of an optical fiber doped with rare earth elements and optically pumped by diodes.




### **Yellow Laser - 577 nm Wavelength:**

Presented as the most versatile wavelength in the scientific literature, the 577 nm wavelength offers the following benefits:

- Excellent combined absorption by both melanin and oxyhemoglobin (peak absorption of oxyhemoglobin) [1,2]
- Very little absorption by macular xanthophyll pigments [1,2]
- Excellent penetration through cataracts and hazy media [1,2].

1- Vogel M, Schäfer FP, Stuke M, Müller K, Theuring S, Morawietz A. Animal, experiments for the determination of an optimal wavelength for retinal coagulations. *Graefes Arch Clin Exp Ophthalmol.* 1989;27:277-280.  
 2- Mainster MA. Wavelength selection in macular photocoagulation. *Tissue optics, thermal effects, and laser systems.* *Ophthalmology.*1986;93:952-958.



# Peripheral and Macular Photocoagulation

## EASYRET®: FULLY INTEGRATED DESIGN

Easyret® offers a fully integrated design in which the laser and the slit lamp are optimally integrated for better ergonomics and ease of use. It is available with two types of slit lamps to adapt to the operator's working habits.

Both versions feature:

- An integrated laser adapter featuring a continuously variable parfocal zoom
- A large touch screen interface to monitor the treatment settings
- A click wheel to control the patterns settings
- An intelligent footswitch to control the laser settings.

Haag Streit Type



## EASYRET®: ENHANCED SOFTWARE USER INTERFACE

### 3 Treatment Modes/3 Dedicated Targets:

Easyret® provides an intuitive and versatile software user interface simplifying the use of the SingleSpot, MultiSpot and SubLiminal® treatment modes. Built in a clinically oriented manner, Easyret® offers 3 different types of visible targets (aiming beam) facilitating the implementation of the laser spots with each treatment mode.

### SingleSpot Mode



### MultiSpot Mode



### SubLiminal® Mode



## MOSAR®: A HIGH DEFINITION IMAGING SYSTEM FOR EASYRET®

Mosar® is an optional camera/video imaging system compatible with the Easyret® laser.

It features:

- A co-observation teaching mode for live viewing of laser procedures
- An advanced mode allowing the operator to:
  - Import diagnosis images facilitating the laser treatment planning
  - Prepare, print and record advanced treatment reports including fundus and diagnosis images
  - Take pictures or record treatment videos for presentation and training purposes.

After each treatment all the generated images, videos and treatment reports can be saved and exported on a USB drive or a local network.

Zeiss Type




## MultiSpot Technology:

Characterized by the use of short pulse durations from 10 to 20 ms, this technology offers many advantages over classical treatments:

- Less heat diffusion to the retina and choroid, less damage to the retinal nerve fiber layer [3,4]
- Comfortable treatment better tolerated by patients [5]
- Treatment time reduction (full PRP in 1 session) [6].

It can be delivered through 4 customizable patterns for better adaptation to the treatment site.




### MultiSpot Panphotocoagulation

Image courtesy of Alejandro Filloy Ruis, MD, Ph.D. Tarragona, Spain


## SubLiminal® Technology:

Composed of a train of extremely short microsecond pulses, this subthreshold treatment mode (non-visible laser impacts) allows the operator to fully adjust the pulse duration (On Time) and interval (Off Time). This finely-tuned control of the laser treatment settings ensures a precise management of the thermal effect on the targeted tissues. It can be delivered through 3 customizable patterns:




Studies using this tissue sparing treatment mode avoiding scarring [7,8] have reports successful outcomes for diabetic macular edema [7] and central serous chorioretinopathy [8].

### Extrafoveal Diabetic Macular Edema




### Central Diabetic Macular Edema

Laser treatment after intravitreal injection



### Chronic Central Serous Chorioretinopathy



Images courtesy of Alejandro Filloy Rius, MD, Ph.D - Tarragona, Spain



## TECHNICAL SPECIFICATIONS

### EASYRET SPECIFICATIONS

Laser source:	fiber laser technology
Wavelength:	yellow 577 nm
Power at tissue up to:	2000 mW
Pulse duration:	10 ms to continuous
Single spot modes:	single, repeat, painting, continuous
SubLiminal® mode:	train of microsecond pulses adjustable duty cycle: 5% to 100% available in MultiSpot and SubLiminal® modes
Resume® function:	
<b>Pattern:</b>	
MultiSpot mode:	single spot, squares, circles, triple arc, macular grid
SubLiminal® mode:	single spot, squares, customizable macular grid
<b>Spot size:</b>	
Single spot:	continuously variable from 50 µm to 400 µm
Pattern:	continuously variable from 100 µm to 400 µm
<b>Integrated slit lamps:</b>	
Haag Streit type:	Quantel Medical (CSO 9900 5x)
Zeiss type:	Quantel Medical (CSO 9800 5x)
Aiming beam:	635 - 650 nm
Size:	174.2 (H) x 97 (W) x 72 (D) cm 68.58" (H) x 38.19" (W) x 28.35" (D)
Weight:	60 kg - 132 lbs
Cooling:	by Peltier effect
Power requirements:	100 to 240 VAC, 250 VA, 50/60 Hz

### OPTIONAL FEATURES

Single column stand or Twin column stand  
Easyret® with LIO port  
Laser indirect ophthalmoscope Keeler Vantage Plus

### MOSAR SPECIFICATIONS

<b>Camera:</b>	
Image resolution:	1280 x 720 pixels
Compatibility:	Easyret® laser
Camera position:	left or right eye
<b>Computer and screen:</b>	
Connected on Easyret® screen arm	
Touchscreen size:	10.1"
Storage:	SSD 256 GB
Connectivity:	USB and Ethernet
Power supply:	12 VDC / 5A

### BIBLIOGRAPHY

- 3- Jain A, Blumenkranz MS, Paulus Y et al. Effect of pulse duration on size and character of the lesion in retinal photocoagulation. Arch Ophthalmol. 2008; 126:78-85.
- 4- Yi-Ryeung Park, Donghyun Jee. Changes in Peripapillary Retinal Nerve Fiber Layer Thickness after Pattern Scanning Laser Photocoagulation in Patients with Diabetic Retinopathy. Korean J Ophthalmol 2014;28(3):220-225.
- 5- Hussainy S Al, Dodson PM and Gibson JM Pain response and follow-up of patients undergoing panretinal laser photocoagulation with reduced exposure times. Eye (2008) 22, 96-99
- 6- Muqit MM, Marcellino GR, Henson DB et al. Single-Session vs Multiple-Session Pattern Scanning Laser Panretinal Photocoagulation in Proliferative Diabetic. Arch ophthalmol, 2010, 128 : 525-533
- 7- Yoon Hyung Kwon, Dong Kyu Lee, Oh Woong Kwon The short-term efficacy of subthreshold micropulse yellow (577 nm) laser photocoagulation for diabetic macular edema. Korean J Ophthalmol 2014;28(5):379-385
- 8- Scholz P, Ersoy L, Boon CJF, Fauser S Subthreshold Micropulse Laser (577 nm). Treatment in Chronic Central Serous Chorioretinopathy. Ophthalmologica 2015 DOI: 10.1159/000439600

Specifications are subject to change without notice.  
©2019. Quantel Medical, Easyret and Resume Function are registered trademarks of Quantel Medical. Elba is a trademark of Quantel. All rights reserved.



PREMED PHARMA KFT.  
CÍM 2040 Budaörs, Gyár u. 2.  
TELEFON 06 23 889 700  
FAX 06 23 889 710  
E-MAIL info@premedpharma.hu  
WEB www.premedpharma.hu

www.quantel-medical.com



Quantel  
BY LUMIBIRD  
ISO 9001 : 2015 – ISO 13485 : 2016

**Headquarters**  
Quantel Medical  
11, rue du Bois Joli - CS40015  
63808 Cournon d'Auvergne – FRANCE  
Tel: +33 (0)4 73 745 745  
Email: contact@quantel-medical.fr

**North America**  
Quantel Medical USA  
2313 Ridge Road Suite 105A  
Rockwall, TX 75087 – USA  
Tel: +1 888 660 6726  
Email: info@quantelmedical.com

**Poland**  
Quantel Medical  
ul. Raclawicka 93  
02-634 Warszawa - POLAND  
Tel: +48 22 5210111  
Email: info@quantel-medical.pl

**Representative Offices**  
Thailand, Chiang Mai  
Brazil, Rio De Janeiro